

INDUSTRIAL COMPONENT DATA

SL7-AP120-E 171285 Y7-171285 EATON ELECTRIC Acoustic module 120 V continuous or pulsed tone external actuati..

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-AP120-E



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-AP120-E
Catalog number	Y7-171285
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-4F9CF8C9D8
Generated	2026-08-04

Product Overview

Acoustic module;120 V;continuous or pulsed tone;external actuation

SL7-AP120-E

Eaton Moeller® series SL7 Acoustic module;120 V;continuous or pulsed tone;external actuation

Acoustic module, 110/120 V AC, continuous or pulsed tone, external actuation, sound pressure 100 db, adjustable with internal potentiometer, f = 2.8kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Acoustic module Catalog Number 171285 Model Code SL7-AP120-E EAN 4015081678303 Product Length/Depth 73 mm Product Height 71 mm Product Width 73 mm Product Weight 0.103 kg

Certifications CSA Class No.: NKCR7

UL

UL 508

CE

UL report applies to both US and Canada

CSA-C22.2 No. 14-10

UL Category Control No.: NKCR

IEC/EN 60947-5-1

IEC/EN 60529

Certified by UL for use in Canada

UL File No.: E29184

CSA-C22.2 No. 94-91 Features & Functions

Color Black Features Sound pressure adjustable to a minimum of 88 dB Functions Continuous tone/pulse tone General

Alarm type 2 types of sound

Can be externally actuated

Tone adjustable

Continuous tone

Pulsed tone Connection to SmartWire-DT No Current consumption 0.041 A, at 110/120 V AC Degree of protection IP66

NEMA 13 Frequency rating 2800 Hz Loudness Can be adjusted with built-in potentiometer

100 dB Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required

Place only at the highest position on a pole Overvoltage category III Pollution degree 3 Product Category SL signal towers

Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to

IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Acoustic module Voltage type AC

Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-AP120-E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.