

INDUSTRIAL COMPONENT DATA

SL4-AP120 171380 Y7-171380 EATON ELECTRIC Acoustic module 120 V continuous or pulsed tone

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-AP120



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-AP120
Catalog number	Y7-171380
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-C5FB3F56FE
Generated	2026-08-04

Product Overview

Acoustic module;120 V;continuous or pulsed tone

SL4-AP120

Eaton Moeller® series SL4 Acoustic module;120 V;continuous or pulsed tone

Acoustic module, 110/120 V AC, continuous tone or pulsed tone, adjustable with internal dip switches, sound pressure 80 db, adjustable with internal potentiometer, f = 4kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Acoustic module Catalog Number 171380 Model Code SL4-AP120 EAN 4015081679096 Product Length/Depth 43 mm Product Height 72 mm Product Width 43 mm Product Weight 0.046 kg

Certifications UL File No.: E29184

Certified by UL for use in Canada

CE

UL 508

IEC/EN 60947-5-1

IEC/EN 60529

UL Category Control No.: NKCR

CSA-C22.2 No. 14-10

UL report applies to both US and Canada

CSA Class No.: NKCR7

UL

CSA-C22.2 No. 94-91 Features & Functions

Color Black Functions Continuous tone/pulse tone General

Alarm type 2 types of sound

Continuous tone

Tone adjustable

Pulsed tone

Internal sound setting, 1 pole DIP Connection to SmartWire-DT No Current consumption 0.021 A, at 110/120 V AC Degree of protection NEMA 13

IP66 Frequency rating 4000 Hz Loudness 80 dB Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required

Place only at the highest position on a pole Overvoltage category III Pollution degree 3 Product Category SL signal towers

Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Acoustic module Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Electrical rating

Lea...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-AP120 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.