

## INDUSTRIAL COMPONENT DATA

# SL7-AP230-E 171286 Y7-171286 EATON ELECTRIC Acoustic module 230 V continuous or pulsed tone external actuati..

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-AP230-E



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | EATON - MOELLER                  |
| MPN / Reference | SL7-AP230-E                      |
| Catalog number  | Y7-171286                        |
| Category        | Acoustic module for signal tower |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-DC31D9B93F                    |
| Generated       | 2026-08-03                       |

## Product Overview

Acoustic module;230 V;continuous or pulsed tone;external actuation

SL7-AP230-E

Eaton Moeller® series SL7 Acoustic module;230 V;continuous or pulsed tone;external actuation

Acoustic module, 230/240 V AC, continuous or pulsed tone, external actuation, sound pressure 100 db, adjustable with internal potentiometer, f = 2.8kHz, IP66

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Acoustic module Catalog Number 171286 Model Code SL7-AP230-E EAN 4015081678310 Product Length/Depth 73 mm Product Height 71 mm Product Width 73 mm Product Weight 0.103 kg

Certifications IEC/EN 60947-5-1

Certified by UL for use in Canada

CSA Class No.: NKCR7

CSA-C22.2 No. 94-91

IEC/EN 60529

UL report applies to both US and Canada

CSA-C22.2 No. 14-10

CE

UL 508

UL File No.: E29184

UL

UL Category Control No.: NKCR Features & Functions

Color Black Features Sound pressure adjustable to a minimum of 88 dB Functions Continuous tone/pulse tone General

Alarm type 2 types of sound

Pulsed tone

Can be externally actuated

Continuous tone

Tone adjustable Connection to SmartWire-DT No Current consumption 0.043 A, at 230/240 V AC Degree of protection

NEMA 13

IP66 Frequency rating 2800 Hz Loudness Can be adjusted with built-in potentiometer

100 dB Material Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC) Mounting position Place only at the highest position on a pole

As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated

impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27,

Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Type Acoustic module Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing D...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-AP230-E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.