

INDUSTRIAL COMPONENT DATA

SL7-AP230 171283 Y7-171283 EATON ELECTRIC Acoustic module 230 V continuous or pulsed tone

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-AP230



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-AP230
Catalog number	Y7-171283
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-F78FF86AFC
Generated	2026-08-05

Product Overview

Acoustic module;230 V;continuous or pulsed tone

SL7-AP230

Eaton Moeller® series SL7 Acoustic module;230 V;continuous or pulsed tone

Acoustic module, 230/240 V AC, continuous tone or pulsed tone, adjustable with internal dip switches, sound pressure 100 db, adjustable with internal potentiometer, f = 2.8kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Acoustic module Catalog Number 171283 Model Code SL7-AP230 EAN

4015081678129 Product Length/Depth 73 mm Product Height 71 mm Product Width 73 mm Product Weight 0.103 kg

Compliances CE Marked Certifications CSA Certified

cULus Listed

UL 508

UL Listed

CSA Std. C22.2 No. 14-10

CSA Class No. NKCR7

UL Listed file E29184

CSA Std. C22.2 No. 94-91

IEC Rated

UL

UL report applies to both US and Canada

UL File No.: E29184

CE

CSA Class No.: NKCR7

IEC/EN 60529

Certified by UL for use in Canada

UL Category Control No.: NKCR

CSA-C22.2 No. 14-10

IEC/EN 60947-5-1

CSA-C22.2 No. 94-91 Catalog Notes 0 Features & Functions

Color Black Features Sound pressure adjustable to a minimum of 88 dB Functions Continuous tone/pulse tone General

Accessories Internal DIP switch, internal potentiometer Alarm type Pulsed tone

Tone adjustable

2 types of sound

Continuous tone

Internal sound setting, 1 pole DIP Connection to SmartWire-DT No Current consumption 0.043 A, at 230/240 V AC Degree of protection NEMA 13

IP66 Frequency rating 2800 Hz Loudness Can be adjusted with built-in potentiometer

100 dB Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position Place only at the highest position on a pole

As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Si...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-AP230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.