

INDUSTRIAL COMPONENT DATA

SL7-AP230-M 171289 Y7-171289 EATON ELECTRIC Acoustic module 230 V multi-tone

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-AP230-M



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-AP230-M
Catalog number	Y7-171289
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-859280F616
Generated	2026-08-05

Product Overview

Acoustic module;230 V;multi-tone

SL7-AP230-M

Eaton Moeller® series SL7 Acoustic module;230 V;multi-tone

Acoustic module, 230/240 V AC, multi-tone (8 tones) adjustable with internal dip switch, sound pressure 100 db, adjustable with internal potentiometer, f = 0.5 - 2.7kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Acoustic module Catalog Number 171289 Model Code SL7-AP230-M EAN 4015081678334 Product Length/Depth 73 mm Product Height 71 mm Product Width 73 mm Product Weight 0.103 kg

Compliances CE Marked Certifications UL 508

CSA Certified

UL Listed

cULus Listed

CSA Std. C22.2 No. 14-10

UL Listed file E29184

CSA Std. C22.2 No. 94-91

CSA Class No. NKCR7

IEC Rated

CSA-C22.2 No. 94-91

IEC/EN 60529

UL

Certified by UL for use in Canada

IEC/EN 60947-5-1

UL report applies to both US and Canada

UL File No.: E29184

UL Category Control No.: NKCR

CSA Class No.: NKCR7

CE

CSA-C22.2 No. 14-10 Catalog Notes 0 Features & Functions

Color Black Features Sound pressure adjustable to a minimum of 88 dB Functions Other General

Accessories Internal DIP switch, internal potentiometer Alarm type Continuous tone

Internal sound setting, 3 pole DIP

Pulsed tone

8 types of sound

Tone adjustable Connection to SmartWire-DT No Current consumption 0.043 A, at 230/240 V AC Degree of protection IP66

NEMA 13 Frequency rating 500 - 2700 Hz Loudness 100 dB

Can be adjusted with built-in potentiometer Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required

Place only at the highest position on a pole Overvoltage category III Pollution degree 3 Product Category SL signal towers

Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to

IEC/EN 60068-2-27

15 g, Mechanical, Acco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-AP230-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.