

INDUSTRIAL COMPONENT DATA

SL7-AP24-E 171284 Y7-171284 EATON ELECTRIC Acoustic module 24 V continuous or pulsed tone external actuation

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-AP24-E



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-AP24-E
Catalog number	Y7-171284
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-D5BBE0ADDD
Generated	2026-08-02

Product Overview

Acoustic module;24 V;continuous or pulsed tone;external actuation

SL7-AP24-E

Eaton Moeller® series SL7 Acoustic module;24 V;continuous or pulsed tone;external actuation

Acoustic module, 24 V AC/DC AC/DC, continuous or pulsed tone, external actuation, sound pressure 100 db, adjustable with internal potentiometer, f = 2.8kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Acoustic module Catalog Number 171284 Model Code SL7-AP24-E EAN 4015081678297 Product Length/Depth 73 mm Product Height 71 mm Product Width 73 mm Product Weight 0.101 kg
Compliances CE Marked Certifications CSA Certified

UL Listed

UL 508

cULus Listed

CSA Std. C22.2 No. 14-10

CSA Std. C22.2 No. 94-91

CSA Class No. NKCR7

UL Listed file E29184

IEC Rated

UL

CSA-C22.2 No. 14-10

CSA-C22.2 No. 94-91

UL report applies to both US and Canada

CSA Class No.: NKCR7

UL File No.: E29184

UL Category Control No.: NKCR

IEC/EN 60529

IEC/EN 60947-5-1

CE

Certified by UL for use in Canada Catalog Notes 0 Features & Functions

Color Black Features Sound pressure adjustable to a minimum of 88 dB Functions Continuous tone/pulse tone Number of modules 2 General

Accessories Internal potentiometer Alarm type Tone adjustable

2 types of sound

Can be externally actuated

Pulsed tone

Continuous tone Connection to SmartWire-DT No Current consumption 0.092 A, at 24 V AC/DC Degree of protection

NEMA 13

IP66 Frequency rating 2800 Hz Loudness 100 dB

Can be adjusted with built-in potentiometer Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position As required

Place only at the highest position on a pole Overvoltage category III Pollution degree 3 Product Category SL signal towers

Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to

IEC/EN 60068-2-27

15 g, Mechanical, A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-AP24-E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.