

INDUSTRIAL COMPONENT DATA

SL7-AP24 171281 Y7-171281 EATON ELECTRIC Acoustic device, 24V, continuous or pulsed tone

Brand: EATON - MOELLER | Manufacturer Part Number: SL7-AP24



Manufacturer	EATON - MOELLER
MPN / Reference	SL7-AP24
Catalog number	Y7-171281
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-EEBDF48BDF
Generated	2026-08-04

Product Overview

Acoustic device, 24V, continuous or pulsed tone

SL7-AP24

Eaton Moeller® series SL7 Acoustic device, 24V, continuous or pulsed tone

Acoustic module, 24 V AC/DC AC/DC, continuous tone or pulsed tone, adjustable with internal dip switches, sound pressure 100 db, adjustable with internal potentiometer, f = 2.8kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL7 Acoustic module Catalog Number 171281 Model Code SL7-AP24 EAN

4015081678105 Product Length/Depth 73 mm Product Height 71 mm Product Width 73 mm Product Weight 0.101 kg

Certifications IEC/EN 60529

CSA-C22.2 No. 14-10

CSA-C22.2 No. 94-91

UL File No.: E29184

CSA Class No.: NKCR7

CE

UL 508

UL Category Control No.: NKCR

IEC/EN 60947-5-1

UL report applies to both US and Canada

Certified by UL for use in Canada

UL Features & Functions

Color Black Features Sound pressure adjustable to a minimum of 88 dB Functions Continuous tone/pulse tone General

Alarm type Internal sound setting, 1 pole DIP

Continuous tone

Tone adjustable

Pulsed tone

2 types of sound Connection to SmartWire-DT No Current consumption 0.092 A, at 24 V AC/DC Degree of protection IP66

NEMA 13 Frequency rating 2800 Hz Loudness 100 dB

Can be adjusted with built-in potentiometer Material Enclosure: Polycarbonate (PC)

Cap: Polycarbonate (PC) Mounting position Place only at the highest position on a pole

As required Overvoltage category III Pollution degree 3 Product Category SL signal towers Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Acoustic module Voltage type AC/DC

Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL7-AP24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.