

INDUSTRIAL COMPONENT DATA

SL4-AP24 171379 Y7-171379 EATON ELECTRIC Acoustic module 24 V continuous or pulsed tone

Brand: EATON - MOELLER | Manufacturer Part Number: SL4-AP24



Manufacturer	EATON - MOELLER
MPN / Reference	SL4-AP24
Catalog number	Y7-171379
Category	Acoustic module for signal tower
Minimum order	1 Pcs
Document ID	EO-E047CC2EDB
Generated	2026-08-05

Product Overview

Acoustic module;24 V;continuous or pulsed tone

SL4-AP24

Eaton Moeller® series SL4 Acoustic module;24 V;continuous or pulsed tone

Acoustic module, 24 V AC/DC, continuous tone or pulsed tone, adjustable with internal dip switches, sound pressure 80 db, adjustable with internal potentiometer, f = 4kHz, IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series SL4 Acoustic module Catalog Number 171379 Model Code SL4-AP24 EAN 4015081679089 Product Length/Depth 43 mm Product Height 72 mm Product Width 43 mm Product Weight 0.046 kg

Certifications UL report applies to both US and Canada

CSA-C22.2 No. 94-91

IEC/EN 60529

UL File No.: E29184

Certified by UL for use in Canada

CSA Class No.: NKCR7

CSA-C22.2 No. 14-10

IEC/EN 60947-5-1

UL
UL 508
UL Category Control No.: NKCR
CE Features & Functions
Color Black Functions Continuous tone/pulse tone General
Alarm type Pulsed tone
Continuous tone
Internal sound setting, 1 pole DIP
2 types of sound
Tone adjustable Connection to SmartWire-DT No Current consumption 0.039 A, at 24 V AC/DC Degree of protection NEMA 13
IP66 Frequency rating 4000 Hz Loudness 80 dB Material Enclosure: Polycarbonate (PC)
Cap: Polycarbonate (PC) Mounting position As required
Place only at the highest position on a pole Overvoltage category III Pollution degree 3 Product Category SL signal towers
Radiation angle 360 ° Rated impulse withstand voltage (Uimp) 4000 V AC Shock resistance Mechanical, According to IEC/EN 60068-2-27
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Type Acoustic module Voltage type AC/DC
Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Electrical rating
Lea...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SL4-AP24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.