

INDUSTRIAL COMPONENT DATA

M22-AMC 229015 Y7-229015 EATON ELECTRIC Acoustic device, compact, IP40 x

Brand: EATON - MOELLER | Manufacturer Part Number: M22-AMC



Manufacturer	EATON - MOELLER
MPN / Reference	M22-AMC
Catalog number	Y7-229015
Category	Acoustic indicator
Minimum order	1 Pcs
Document ID	EO-F0B184B61C
Generated	2026-08-02

Product Overview

Acoustic device, compact, IP40_x

M22-AMC

Eaton Moeller® series M22 Acoustic device, compact, IP40_x

Acoustic device, RMQ system, without buzzer with lamp holder BA9s, front black, compact, degree of protection IP40

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Accessory Acoustic indicator

Catalog Number 229015

Model Code M22-AMC

EAN 4015082290153

Product Length/Depth 62 mm

Product Height 30 mm

Product Width 30 mm

Product Weight 0.024 kg

Compliances CE Marked

Certifications CSA Std. C22.2 No. 94-91

UL 508

IEC 60947-5

EN 60947-5

CSA Std. C22.2 No. 14-05

VDE

CSA-C22.2 No. 94-91

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR

CE

CSA File No.: 012528

IEC/EN 60947

VDE 0660

IEC/EN 60947-5

CSA Class No.: 3211-03

UL File No.: E29184

UL

CSA

Catalog Notes without buzzer

Features & Functions

Color Black

Fitted with: BA 9s lamp socket

Loudness 0 dB

General information

Degree of protection IP40

NEMA 4X, 13

Overvoltage category III

Pollution degree 3

Product Category Accessories

Product Category Accessories

Rated impulse withstand voltage (Uimp) 4000 V AC

Type Compact

Voltage type AC/DC

Ambient conditions, mechanical

Mounting position As required

Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 70 °C

Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

Terminal capacity (solid) 2 x (0.5 - 1.5) mm²

Terminal capacity (stranded) 0.5 - 1.5 mm²

Electrical rating

Rated insulation voltage (Ui) 250 V

Rated operational voltage (Ue) at AC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-AMC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.