

INDUSTRIAL COMPONENT DATA

HH-K 063267 EATON ELECTRIC Actuating rod insulated material

Brand: EATON - MOELLER | Manufacturer Part Number: HH-K



Manufacturer	EATON - MOELLER
MPN / Reference	HH-K
Catalog number	063267
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-744E5026B4
Generated	2026-08-02

Product Overview

Actuating rod insulated material

Drive head; Insulating actuating rod

Actuating rod, Components, Part group reference: AT4, Function: Actuating rod, Description: For adding R-AT4 rotary drive, With plastic rod, Not to be used as a safety position switch, Max. operating speed lateral: 1.4, Lever length: 190 mm, For use with: R-AT4, Snap-action contact: Only permissible with snap-action contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

EL-Nummer (Norway)4355957Actuating rod insulated materialActuating rod, Components, Part group reference: AT4, Function: Actuating rod, Description: For adding R-AT4 rotary drive, With plastic rod, Not to be used as a safety position switch, Max. operating speed lateral: 1.4, Lever length: 190 mm, For use with: R-AT4, Snap-action contact: Only permissible with snap-action contactDelivery program

Basic functionComponentsPart group referenceAT4Product rangeActuatorsFunctionActuating rodDescriptionFor adding R-AT4 rotary drive

With plastic rod

Not to be used as a safety position switchMax. operating speed lateral1.4Lever length [l]190 mmFor use

withR-AT4Snap-action contactOnly permissible with snap-action contactDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation,

non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+70 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / HH-K with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.