

INDUSTRIAL COMPONENT DATA

AD20 EATON ELECTRIC Fuse-link, low voltage, 20 A, AC 550 V, BS88, 21 x 129 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: AD20



Manufacturer	EATON - MOELLER
MPN / Reference	AD20
Catalog number	10000
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-0DBCEAB830
Generated	2026-08-06

Product Overview

20Amp 550Vac / 250Vdc INDUSTRIAL FUSE

Eaton Bussmann series low voltage British standard fuse, 20 A, 550 V, 80 kAIC, 3.1 Watt, 111 mm fixing centre Fuse, Fuse-link, low voltage, 20 A, AC 550 V, BS88, 21 x 129 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-1, IEC 60269-1, Breaking Capacity 80 kA, Ceramic body

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number AD20 EAN 5027590491761 UPC 051712838504 Product Length/Depth 129 mm Product Height 21 mm Product Width 22 mm Product Weight 63.15 g

Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 20 A Voltage rating 550 V Voltage type AC

AC/DC Breaking capacity 80 kA Class Class gG/gL Product specifications

Fuse type AD Fitted with: Centre bolted tags Construction BS88

ETIM for AD20 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

550 V

Rated voltage DC (EF012281)

250 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

3.1 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

111 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AD20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.