

INDUSTRIAL COMPONENT DATA

ADE1M200NPN -1F2 NP ISO20 TYP3 ADE1M200NPN CAP806664V1 EATON ELECTRIC ADE1M200NPN -1F2 NP ISO20 TYP3

Brand: EATON - MOELLER | Manufacturer Part Number: ADE1M200NPN -1F2 NP ISO20 TYP3



Manufacturer	EATON - MOELLER
MPN / Reference	ADE1M200NPN -1F2 NP ISO20 TYP3
Catalog number	CAP806664V1
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-F6A6DA2FC1
Generated	2026-08-05

Product Overview

ADE1M200NPN -1F2 NP ISO20 TYP3

Eaton ADE 1F2, Non-armoured, Nickel-plated Brass, M20, 0 (XS), 2.75-5.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER

Additional Product Information

General specifications

Product Name Eaton's Crouse-Hinds series Capri ADE-1F2 cable gland Catalog Number ADE1M200NPN EAN 3589350032390 Product Length/Depth 39 mm Product Height 26.4 mm Product Width 24 mm Product Weight 51 g Product specifications

Area classification Hazardous/Classified Locations Standards type NEC/CEC

IEC

IECEX/ATEX NEC hazardous rating Class I, Zone 1

Class I, Zone 2 Ingress protection (IP) ratings IP68

IP66 IECEX/ATEX hazardous rating Zone 1

Zone 2

Zone 22

Zone 21 Material Nickel plated brass Cable sealing range 0 (XS) Connector type Straight Gland size 3 Gland type

Non-armoured Outer sheath (min/max) 2.75-5.5 Protection type Flameproof and increased safety Sealing type Silicone
Thread Size M20 Nominal thread size Metric/PG 20 Pitch thread 1.5 mm Thread Length 15 mm Wrench width 24 mm
Hexagon angular dimension 26.4 mm Suitable for cable diameter - max 5.5 mm Suitable for cable diameter - min 2.8 mm
Material quality Brass Surface protection Nickel-plated Degree of protection (IP) IP66 Model Straight Type of sealing
Sealing ring Working temperature - max 140 °C Working temperature - min -60 °C For ex-zone gas 1, 2 For ex-zone dust
21, 22 Fitted with: Separable Screw Gland
Strain Relief Integrated function Screened Lamp type included Halogen Free Thread type Metric Protection, proofing and
resistance Shock Resistant Suitable for Armoured Cable Version EMC
Explosion - Tested
ETIM for ADE1M200NPN Cable glands and cable entry products (EC000441)
Feature Name
F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ADE1M200NPN -1F2 NP ISO20 TYP3 with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.