

INDUSTRIAL COMPONENT DATA

LS-XRLA40 266129 Y7-266129 EATON ELECTRIC Adjustable roller lever, D 40mm

Brand: EATON - MOELLER | Manufacturer Part Number: LS-XRLA40



Manufacturer	EATON - MOELLER
MPN / Reference	LS-XRLA40
Catalog number	Y7-266129
Category	Drive head for position switches/hinge switches
Minimum order	5 Pcs
Document ID	EO-4AE9A979DF
Generated	2026-08-01

Product Overview

Adjustable roller lever, D=40mm

LS-XRLA40

Eaton Moeller® series LS Adjustable roller lever, D=40mm

Operating head for LS-Titan position switch, IEC EN 60947-5-1, high degree of protection IP66, device for world markets, modular system, easy mounting technology operating heads can be attached in any 4 directions and snapped on simple, quick and safely using the bayonet fitting.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Adjustable roller lever Catalog Number 266129 Model Code LS-XRLA40 EAN 4015082661298 Product Length/Depth 25 mm Product Height 114 mm Product Width 57 mm Product Weight 0.041 kg

Compliances CE Marked Certifications IEC 60947-5

EN 60947-5

UL 508

CSA Std. C22.2 No. 14

CSA File No.: 012528

IEC/EN 60947-5

CSA

UL

CSA Class No.: 3211-03

CSA-C22.2 No. 14

UL File No.: E29184

CE

UL Category Control No.: NKCR Features & Functions

Features The operating head can be rotated 90° to enable adaptation to the specified approach direction General

Product category Adjustable roller lever Type Operating heads Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 70 °C Actuator

Actuator diameter 40 mm Actuator type Adjustable roller lever Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. ef...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-XRLA40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.