

INDUSTRIAL COMPONENT DATA

LS-XRLA40R 266130 Y7-266130 EATON ELECTRIC Adjustable roller lever, D 40mm, rubber

Brand: EATON - MOELLER | Manufacturer Part Number: LS-XRLA40R



Manufacturer	EATON - MOELLER
MPN / Reference	LS-XRLA40R
Catalog number	Y7-266130
Category	Drive head for position switches/hinge switches
Minimum order	5 Pcs
Document ID	EO-E2A1616D43
Generated	2026-08-02

Product Overview

Adjustable roller lever, D=40mm, rubber

LS-XRLA40R

Eaton Moeller® series LS Adjustable roller lever, D=40mm, rubber

Operating head for LS-Titan position switch, IEC EN 60947-5-1, high degree of protection IP66, device for world markets, modular system, easy mounting technology operating heads can be attached in any 4 directions and snapped on simple, quick and safely using the bayonet fitting.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Adjustable roller lever Catalog Number 266130 Model Code LS-XRLA40R EAN 4015082661304 Product Length/Depth 25 mm Product Height 114 mm Product Width 57 mm Product Weight 0.043 kg

Compliances CE Marked Certifications EN 60947-5

CSA Std. C22.2 No. 14

UL 508

IEC 60947-5

VDE

CSA File No.: 012528

UL Category Control No.: NKCR

CE

CSA

CSA-C22.2 No. 14

IEC/EN 60947-5

UL File No.: E29184

CSA Class No.: 3211-03

UL Features & Functions

Features The operating head can be rotated 90° to enable adaptation to the specified approach direction Material Rubber roller

Rubber (Roller) General

Product category Adjustable roller lever Type Operating heads Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 70 °C Actuator

Actuator diameter 40 mm Actuator type Adjustable roller lever Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-XRLA40R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.