

INDUSTRIAL COMPONENT DATA

AFDD-25/2/C/003-LI/A 187229 Y7-187229 EATON ELECTRIC Auxiliary contact module, 1N/O early+1N/C late, surface..

Brand: EATON - MOELLER | Manufacturer Part Number: AFDD-25/2/C/003-LI/A



Manufacturer	EATON - MOELLER
MPN / Reference	AFDD-25/2/C/003-LI/A
Catalog number	Y7-187229
Category	Earth leakage circuit breaker with auxiliary device
Minimum order	1 Pcs
Document ID	EO-0CBCE76CE2
Generated	2026-08-06

Product Overview

Auxiliary contact module, 1N/O early+1N/C late, surface mounting, spring clamp connection

Arc flash fault switch, 2-pole, C25A, 30mA, type LI/A

Arc Fault Detection Device, 2p, C, 25 A, 30 mA, type LI/A

Arc Fault Detection Device (AFDD) with residual current device/miniature circuit breaker combination, conforms to IEC/EN 62606, reliably detects arc faults, residual current circuit-breaker part is line voltage-independent, optionally pulse-current sensitive, delayed or non-delayed, contact position indicator red - green, trip indication with LED, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, rated fault currents: 10 mA or 30 mA, rated operational currents up to 40 A, tripping characteristics B, C, rated breaking capacity up to 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

EL-Nummer (Norway)1601448Arc Fault Detection Device, 2p, C, 25 A, 30 mA, type LI/AArc Fault Detection Device (AFDD) with residual current device/miniature circuit breaker combination, conforms to IEC/EN 62606, reliably detects arc faults, residual current circuit-breaker part is line voltage-independent, optionally pulse-current sensitive, delayed or non-delayed, contact position indicator red - green, trip indication with LED, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, rated fault currents: 10 mA or 30 mA, rated operational currents up to 40 A, tripping characteristics B, C, rated breaking capacity up to

10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C Delivery program
Basic function Arc fault detection device Number of poles 2 pole Tripping characteristic C Application Switchgear for residential
and commercial applications Rated current [In] 25 A Rated switching capacity according to IEC/EN 60898-1 [Icn] 10 kA Rated
switching capacity according to IEC/EN 61009-1 10 kA Rated short-circuit strength [Icn] 10 kA Rated fault current [I_N] 0.03
A Type Type LI/A Tripping Short time-delayed s... Busbar type ZV-SS Product range AFDD Sensitivity Pulse-current
sensitive Impulse withstand current Partly surge-proof 250 A Technical data
Electrical Types conform to IEC/EN 62606
IEC/EN 61009 Current test marks As per inscription Rated switching capacity acc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AFDD-25/2/C/003-LI/A with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.