

INDUSTRIAL COMPONENT DATA

AFDD-6/2/C/003-F MB-300178 Y7-300178 EATON ELECTRIC Fire Protection Switch, 2p, C, 6 A, 30 mA, Type F

Brand: EATON - MOELLER | Manufacturer Part Number: AFDD-6/2/C/003-F



Manufacturer	EATON - MOELLER
MPN / Reference	AFDD-6/2/C/003-F
Catalog number	Y7-300178
Category	Earth leakage circuit breaker with auxiliary device
Minimum order	1 Pcs
Document ID	EO-8E86567664
Generated	2026-08-02

Product Overview

Fire Protection Switch, 2p, C, 6 A, 30 mA, Type F

Arc Fault Detection Device, 2p, C, 6 A, 30 mA, type F

High-quality arc fault detection device (AFDD) with residual current device/miniature circuit breaker combination, line voltage-independent, contact position indicator red - green, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, wide range of rated fault currents, rated operational currents up to 40 A, tripping characteristics B, C, D, rated breaking capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Tertiary and Differential

Additional Product Information

Arc Fault Detection Device, 2p, C, 6 A, 30 mA, type FHigh-quality arc fault detection device (AFDD) with residual current device/miniature circuit breaker combination, line voltage-independent, contact position indicator red - green, terminal rear plug protection, tri-stable slide catch - enables removal from existing busbar system, comprehensive range of accessories suitable for subsequent installation, wide range of rated fault currents, rated operational currents up to 40 A, tripping characteristics B, C, D, rated breaking capacity 10 kA, suitable for outdoor use (on-site power and outdoor distribution board) up to -25 °C

General specificationsProduct nameEaton Moeller series xPole - AFDD+ Arc fault detection devicePart no.AFDD-6/2/C/003-FEAN9010238802193Product Length/Depth80 millimetreProduct height73 millimetreProduct width52.5 millimetreProduct weight0.277 kilogramCompliancesCE Marked

RoHS conformCertificationsCEProduct TradenamexPole - AFDD+Product TypeArc fault detection deviceProduct Sub TypeNoneDelivery programApplicationSwitchgear for residential and commercial applicationsProduct rangeAFDDBasic functionArc fault circuit interrupterProduct applicationSwitchgear for residential and commercial applicationsNumber of polesTwo-poleRelease characteristicCTripping characteristicCRated current6 ARated current of product range6-40 AmpereFault current rating0.03 ASensitivity typeType F Pulse-current sensitive up to 1 kHz and <=10 mA smooth DC currentTypeAFDD+Technical Data....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AFDD-6/2/C/003-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.