

INDUSTRIAL COMPONENT DATA

AGM2-01-PKZ0-PI 199330 Y7-199330 EATON ELECTRIC

AGM2-01-PKZ0-PI

Brand: EATON - MOELLER | Manufacturer Part Number: AGM2-01-PKZ0-PI



Manufacturer	EATON - MOELLER
MPN / Reference	AGM2-01-PKZ0-PI
Catalog number	Y7-199330
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-F21AE16475
Generated	2026-08-04

Product Overview

AGM2-01-PKZ0-PI

Eaton Moeller® series PKZ Trip indicator, 2 x 1 NC, Push in terminals

Trip indicator switch 2 N/C, Push-In, for circuit-breaker PKZ(M)0 size

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ Trip indicator Catalog Number 199330 Model Code AGM2-01-PKZ0-PI EAN 4015081974146 Product Length/Depth 73 mm Product Height 92 mm Product Width 24 mm Product Weight 0.044 kg

Compliances CE Marked

RoHS conform Certifications CSA File No.: 165628

CSA Class No.: 3211-05

UL File No.: E36332

UL Category Control No.: NLRV

UL 508

CE marking

CSA-C22.2 No. 14

IEC 60947-4-1

UL

CSA Features & Functions

Electric connection type Spring clamp connection Features Interlocked opposing contacts Indication Short-circuits indicated locally by means of a red indicator that can be manually reset General

Lifespan, electrical 50,000 Operations Lifespan, mechanical 10,000 Operations Model Top mounting Mounting method Side mounting Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 6000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (flexible with unisolated ferrule) 1 x (0.5 - 2.5) mm²

2 x (0.5 - 2.5) mm² Terminal capacity (flexible with ferrule) 1 x (0.5 - 1.5) mm²

2 x (0.5 - 1.5) mm² Terminal capacity (flexible) 1 x (0.5 - 2.5) mm²

2 x (0.5 - 2.5) mm² Terminal capacity (solid) 1 x (0.5 - 2.5) mm²

2 x (0.5 - 2.5) mm² Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating

Rated operational current (Ie) 1 A at AC-15, 440 V 500 V Rated operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AGM2-01-PKZ0-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.