

INDUSTRIAL COMPONENT DATA

AKU-M10/10 138361 Y7-138361 EATON ELECTRIC Conductor connection terminal M10 for 10mm

Brand: EATON - MOELLER | Manufacturer Part Number: AKU-M10/10



Manufacturer	EATON - MOELLER
MPN / Reference	AKU-M10/10
Catalog number	Y7-138361
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-6FFBA1A253
Generated	2026-08-06

Product Overview

Conductor connection terminal M10 for 10mm

AKU-M10/10

Eaton xEffect SASy 60i Enclosures Switch- & Controlgear Enclosure. Conductor connection terminal M10 for 10mm Universal conductor connection terminal, cable lugs M10, 630A, can be used for all 10 mm thick flat busbars, double T profile, width=38mm, termination space WxH=M10x10 bolt mm, with integrated retaining spring, with open terminal chamber and captive fixing screw, can be used with

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASy 60i busbar terminal Catalog Number 138361 Model Code AKU-M10/10 EAN 4015081351411 Product Length/Depth 47 mm Product Height 42 mm Product Width 38 mm Product Weight 0.362 kg Compliances RoHS conform Delivery program

Type Technical data - electrical

Rated operation current (Ie) 630 A Rated operational current 630 A Rated operational current (Ie) - max 630 A Technical data - mechanical

Busbar thickness - min 10 mm Busbar thickness - max 10 mm Busbar width - min 0 mm Busbar width - max 0 mm Terminal contact area 10 mm with M10 bolt Terminal capacity (conductor) Cable lugs M10 Conductor cross section - max 0 mm²

Width clamp 38 mm Additional information

Functions Universal conductor connection terminal

Connections Special features With integrated retaining spring, open terminal chamber and captive terminal screw Suitable for Round conductor connection

Flat rail Used with All 10 mm thick flat busbars

Double T profile

ETIM for 138361 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

10 mm

Busbar width (EF007219)

0 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

38 mm

Max. conductor cross section (EF004969)

0 mm²

Max. rated operation current I_e (EF007356)

630 A

Suitable for round conductor connection (EF007258)

Yes

Suitable for sector conductor connection (EF007260)

No

Suitable for strip conductor connection (EF007242)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AKU-M10/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.