

INDUSTRIAL COMPONENT DATA

AKU-M8/10 138362 Y7-138362 EATON ELECTRIC Conductor connection terminal M8 for 10mm

Brand: EATON - MOELLER | Manufacturer Part Number: AKU-M8/10



Manufacturer	EATON - MOELLER
MPN / Reference	AKU-M8/10
Catalog number	Y7-138362
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-A57A0136A6
Generated	2026-08-04

Product Overview

Conductor connection terminal M8 for 10mm

AKU-M8/10

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Conductor connection terminal M8 for 10mm Universal conductor connection terminal, cable lugs M8, 490A, can be used for all 10 mm thick flat busbars, double T profile, width=30mm, termination space WxH=M8x8 bolt mm, with integrated retaining spring, with open terminal chamber and captive fixing screw, can be used with

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i busbar terminal Catalog Number 138362 Model Code AKU-M8/10 EAN 4015081351428 Product Length/Depth 36 mm Product Height 32 mm Product Width 30 mm Product Weight 0.165 kg Compliances RoHS conform Delivery program

Type Technical data - electrical

Rated operation current (Ie) 490 A Rated operational current 490 A Rated operational current (Ie) - max 490 A Technical data - mechanical

Busbar thickness - min 10 mm Busbar thickness - max 10 mm Busbar width - min 0 mm Busbar width - max 0 mm Terminal contact area 8 mm with M8 bolt Terminal capacity (conductor) Cable lugs M8 Conductor cross section - max 0 mm² Width clamp 30 mm Additional information

Functions Connections

Universal conductor connection terminal Special features With integrated retaining spring, open terminal chamber and captive terminal screw Suitable for Flat rail

Round conductor connection Used with Double T profile

All 10 mm thick flat busbars

Compact system

60 mm system

Connection

185 mm system

ETIM for 138362 Low-voltage industrial controls and switchgear (EC000001)

Feature Name

Feature Value

Busbar thickness (EF007220)

10 mm

Busbar width (EF007219)

0 mm

Suitable for (EF000073)

Flat rail

Width clamp (EF007092)

30 mm

Max. conductor cross section (EF004969)

0 mm²

Max. rated operation current I_e (EF007356)

490 A

Suitable for round conductor connection (EF007258)

Yes

Suitable for sector conductor connection (EF007260)

No

Suitable for strip conductor connectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AKU-M8/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.