

INDUSTRIAL COMPONENT DATA

AKU16/10 107191 Y7-107191 EATON ELECTRIC Conductor connection terminal 1.5-16mm², 10 mm

Brand: EATON - MOELLER | Manufacturer Part Number: AKU16/10



Manufacturer	EATON - MOELLER
MPN / Reference	AKU16/10
Catalog number	Y7-107191
Category	Busbar terminal
Minimum order	100 Pcs
Document ID	EO-40E50E58A3
Generated	2026-08-05

Product Overview

Conductor connection terminal 1.5-16mm², 10 mm

AKU16/10

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Conductor connection terminal 1.5-16mm², 10 mm Universal conductor connection terminal, 1.5-16mm² AWG 14-AWG 6., directly terminated, 8x6x0.5, 180A, can be used for all 10mm thick flat busbars, width=11.5mm, termination space WxH=7.5x7.5mm, with integrated retaining spring, with open terminal chamber and captive fixing screw, can be used for SASY60i, SASY185i

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i busbar terminal Catalog Number 107191 Model Code AKU16/10 EAN 4015081069545 Product Length/Depth 12 mm Product Height 25 mm Product Width 23 mm Product Weight 0.021 kg

Compliances UL CSA09 (refer to approbation report)

RoHS conform Certifications UL (File No. E307559)

IEC 60439-1

CSA-C22.2 No. 14

UL508A

CSA (File No. 236217)

CE marking

North America (UL listed, CSA certified)

UL (Category Control Number NMTR2, NMTR8)

CSA (Class No. 3211-37) Delivery program

Type Technical data - electrical

Voltage rating (UL CSA 13) Max. 600 V AC Rated operation current (Ie) 180 A Rated operational current 180 A Rated operational current (Ie) - max 180 A Technical data - mechanical

Degree of protection UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking

Feeder circuits Busbar thickness - min 10 mm Busbar thickness - max 10 mm Busbar width - min 0 mm Busbar width - max 0 mm Terminal contact area 7.5 mm x 7.5 mm Terminal capacity (conductor) AWG 14 - AWG 6

1.5 mm² - 16 mm²

6 mm x 0.5 mm (8x) Conductor cross section - max 16 mm² Width clamp 11.5 mm Additional information

Functions Connections

Current limiting circuit breaker, refer to approbation report

Universal conductor connection terminal Special features With integrated retaining spring, open terminal chamber and captive terminal screw Suitable for Strip conductor connection

Flat rail

Round conductor connection

Sector conductor connection Used with All 10 mm thick flat busbars

Feeder...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AKU16/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.