


INDUSTRIAL COMPONENT DATA

ETS4-VS3 083094 Y7-83094 EATON ELECTRIC Amplifier module, for separate mounting

Brand: EATON - MOELLER | Manufacturer Part Number: ETS4-VS3



Manufacturer	EATON - MOELLER
MPN / Reference	ETS4-VS3
Catalog number	Y7-83094
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-07EF5FE9FB
Generated	2026-07-31

Product Overview

Amplifier module, for separate mounting

Amplifier Module For Stand-Alone Mounting

Eaton Moeller® series Amplifier module, for separate mounting

Interface relays for low-wiring actuation of large contactors

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series amplifier module Catalog Number 083094 Model Code ETS4-VS3 EAN

4015080830948 Product Length/Depth 103 mm Product Height 83 mm Product Width 23 mm Product Weight 0.1 kg

Certifications CSA Class No.: 2411-03, 3211-04

CSA file No. 012528

IEC/EN 60947-4-1

UL 508

CSA-C22.2 No. 14-05

CE marking

IEC/EN 60947

VDE 0660

UL

CSA

UL Category Control No.: NKCR

UL File No.: E29184

UL Listed

CSA certified Catalog Notes Contactor coils with rated operational current > 2 A must be actuated via the DILER-G mini contactor relay. Features & Functions

Fitted with: LED indication General

Accessory/spare part type Other Lifespan 30,000,000 mechanical Operations (DC operated) Mounting method DIN rail

Overvoltage category III Pollution degree 2 Rated impulse withstand voltage (Uimp) 6 kV Used with DILM

DILMP

DILL

DILK

DILMF Voltage type DC Ambient conditions, mechanical

Mounting position As required Shock resistance 10 g, N/O contact, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 20 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 45 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30 Terminal capacities

Terminal capacity 1 x (0.75 - 2.5) mm², solid

2 x (0.75 - 2.5) mm², solid

1 x (0.75 - 2.5) mm², flexibl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ETS4-VS3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.