

INDUSTRIAL COMPONENT DATA

XIOC-2AI-1AO-U1-I1 281545 4519688 EATON ELECTRIC

Analog I/O module for XC100/200, 24 V DC, 2AI, 1AO(0-10V, 0..

Brand: EATON - MOELLER | Manufacturer Part Number: XIOC-2AI-1AO-U1-I1



Manufacturer	EATON - MOELLER
MPN / Reference	XIOC-2AI-1AO-U1-I1
Catalog number	4519688
Category	PLC analogue I/O-module
Minimum order	1 Pcs
Document ID	EO-F2D758C8F4
Generated	2026-08-06

Product Overview

Analog I/O module for XC100/200, 24 V DC, 2AI, 1AO(0-10V, 0-20mA)

XIOC-2AI-1AO-U1-I1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > XC Modular PLC

Additional Product Information

EL-Nummer (Norway)4519688Analog I/O module for XC100/200, 24 V DC, 2AI, 1AO(0-10V, 0-20mA)Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. a particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.Delivery program

FunctionAnalog modulesCompact I/O system for connection to XC100/200 Modular PLCs

XC100/200 expandable with up to 15 XI/OC modules

Optionally, screw terminals or spring-loaded terminals for digital/analog modulesDescriptionCombination modules

2 Inputs and 1 Output 0 - 10 V, 0 - 20 mA

1 ms conversion time

individual changeoverTechnical data

GeneralStandardsIEC/EN 61131-2

EN 50178 Ambient temperature 0 - +55 °C Storage [?] -25 - +70 °C Vibration resistance 10 - 57 Hz ±0.075 mm
57 - 150 Hz ±1.0 mm Mechanical shock resistance 15
Shock duration 11 ms g Impact resistance 500 g/? 50 mm ±25 g Overvoltage category/pollution degree II/2 Protection
class 1 Degree of Protection IP20 Emitted interference DIN/EN 55011/22, Class A Weight 0.16 kg Power supply Rated voltage
[Ue] 24 (12) V DC Admissible range 20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XIOC-2AI-1AO-U1-I1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.