

INDUSTRIAL COMPONENT DATA

XIOC-2AO-U1-2AO-I2 257902 0004519674 EATON ELECTRIC

Analog output module for XC100/200, 24 V DC, 4AO(2x0-10V..

Brand: EATON - MOELLER | Manufacturer Part Number: XIOC-2AO-U1-2AO-I2



Manufacturer	EATON - MOELLER
MPN / Reference	XIOC-2AO-U1-2AO-I2
Catalog number	0004519674
Category	PLC analogue I/O-module
Minimum order	1 Pcs
Document ID	EO-DDAD6D2221
Generated	2026-08-05

Product Overview

Analog output module for XC100/200, 24 V DC, 4AO(2x0-10V, 2x4-20mA)

XIOC-2AO-U1-2AO-I2

Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. a particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > XC Modular PLC**

Additional Product Information

EL-Nummer (Norway)4519674Analog output module for XC100/200, 24 V DC, 4AO(2x0-10V, 2x4-20mA)Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. a particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.Delivery program

FunctionAnalog modulesCompact I/O system for connection to XC100/200 Modular PLCs

XC100/200 expandable with up to 15 XI/OC modules

Optionally, screw terminals or spring-loaded terminals for digital/analog modules

2 Outputs 0 - 10 V

2 outputs 4 - 20 mA

Technical data

General Standards IEC/EN 61131-2

EN 50178 Ambient temperature 0 - +55 °C Storage [-25 - +70 °C

Vibration resistance 10 - 57 Hz ±0.075 mm

57 - 150 Hz ±1.0 mm Mechanical shock resistance 15

Shock duration 11 ms g Impact resistance 500 g/? 50 mm ±25 g

Overvoltage category/pollution degree II/2 Protection

class 1 Degree of Protection IP20 Emitted interference DIN/EN 55011/22, Class A

Weight 0.18 kg Power supply Rated voltage

[Ue] 24 (12) V DC Admissible range 20.4 - 28.8 (11.8 - 14.4)

Residual ripple? 5 % Neutral poles...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XIOC-2AO-U1-2AO-I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.