

INDUSTRIAL COMPONENT DATA

XN-1AO-I(0/4...20MA) 140065 Y7-140065 EATON ELECTRIC

Analog output module XI/ON, 24 V DC, 1AO (0/4 to 20mA)

Brand: EATON - MOELLER | Manufacturer Part Number: XN-1AO-I(0/4...20MA)



Manufacturer	EATON - MOELLER
MPN / Reference	XN-1AO-I(0/4...20MA)
Catalog number	Y7-140065
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-816F9D0AA0
Generated	2026-08-06

Product Overview

Analog output module XI/ON, 24 V DC, 1AO (0/4 to 20mA)

XN-1AO-I(0/4...20MA)

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

EL-Nummer (Norway)4520622Analog output module XI/ON, 24 V DC, 1AO (0/4 to 20mA)The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.Delivery program

FunctionXI/ON I/O modulesFunctionXN Slice moduleShort Description1 Analog outputs

0/4 to 20 mAFor use withXN-S3T-SBB

XN-S3S-SBBTechnical data

GeneralStandardsEN 61000-6-2

EN 61000-6-4

EN 61131-2Potential isolationYes, through optocouplerAmbient temperatureAmbient temperature, operation0 - +55

°CAmbient temperatureStorage, transport [?]-25 - +85 °CRelative humidityRelative humidity5 - 95 % (indoor), Level RH-2,

no condensation (for storage at 45°C) Ambient conditions, mechanical Degree of Protection IP20 Ambient conditions, mechanical Harmful gases SO₂: 10 (rel. humidity < 75%, no condensation)
H₂S: 1.0 (rel. humidity < 75 %, no condensation) ppm Vibration resistance, operating conditions according to IEC/EN 60068-2-6 Mechanical shock resistance according to IEC 60068-2-27 g Continuous shock resistance (IEC/EN 60068-2-29) According to IEC 60068-2-29 Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Electromagnetic compatibility (EMC) ESD [Air/contact discharge] EN 61000-4-2 kV Electromagnetic compatibility (EMC) Electro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-1AO-I(0/4...20MA) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.