

INDUSTRIAL COMPONENT DATA

AT0-11-S-IA/ZS 040816 AT0-11-S-IA-ZS EATON ELECTRIC
Position switch, 1N/O+1N/C, wide, IP65 x, rounded plunge..

Brand: EATON - MOELLER | Manufacturer Part Number: AT0-11-S-IA/ZS



Manufacturer	EATON - MOELLER
MPN / Reference	AT0-11-S-IA/ZS
Catalog number	AT0-11-S-IA-ZS
Category	End switch
Minimum order	1 Pcs
Document ID	EO-CCBFDE0811
Generated	2026-08-06

Product Overview

Position switch, 1N/O+1N/C, wide, IP65_x, rounded plunger, centre fixing

Position switch; 1 NO + 1 NC ; IP65; Box-Broadband; Piston round; central locking

Position switch, Degree of Protection: IP65, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC,

Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Housing: Wide version, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product InformationPosition switch, 1N/O+1N/C, wide, IP65_x, rounded plunger, centre fixingPosition switch, Degree of Protection: IP65,
Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening
to IEC/EN 60947-5-1, Housing: Wide version, Standards: IEC/EN 60947Delivery programDegree of ProtectionIP65ContactsN/O = Normally open1 N/ON/C = Normally closed1 NCNotes=safety function, by positive
opening to IEC/EN 60947-5-1Contact sequenceContact travel? = Contact closed? = Contact openHousingWide
versionTechnical dataGeneralStandardsIEC/EN 60947Climatic proofingDamp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC
60068-2-30Mounting positionAs requiredDegree of ProtectionIP65Terminal capacitiesSolid1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm2Terminal capacitiesFlexible with ferrule1 x (0.5 - 1.5)

2 x (0.5 - 1.5) mm2Repetition accuracy0.02 mmContacts/switching capacityRated impulse withstand voltage [Uimp]6000 V
ACRated insulation voltage [Ui]500 VRated operational current [Ie]AC-1524 V [Ie]10 ARated operational current
[Ie]AC-15220 V 230 V 240 V [Ie]6 ARated operational current [Ie]AC-15380 V 400 V 415 V [Ie]4 ARated operational current

[I_e]DC-1324 V [I_e]10 A Rated operational current [I_e]DC-13110 V [I_e]1 A Rated operational current [I_e]DC-13220 V [I_e]0.5 A Supply frequency max. 400 Hz Short-circuit rating to IEC/EN 60947-5-1 max. fuse 6 A gG/gL Mechanical variables Contact temperature of roller head? 100 °C Mechanical shock resistance (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AT0-11-S-IA/ZS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.