

INDUSTRIAL COMPONENT DATA

AT4/11-2/IA/S 024229 EATON ELECTRIC Position switch, 1early N/O+1late N/C, wide, IP65 x, plunger

Brand: EATON - MOELLER | Manufacturer Part Number: AT4/11-2/IA/S



Manufacturer	EATON - MOELLER
MPN / Reference	AT4/11-2/IA/S
Catalog number	024229
Category	End switch
Minimum order	1 Pcs
Document ID	EO-7798F7F734
Generated	2026-08-05

Product Overview

Position switch, 1early N/O+1late N/C, wide, IP65_x, plunger

Position switch; 1 NOA +1 NCR ; IP65; Box-Broadband; Piston

Position switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Rounded plunger, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50041 Form B, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Color Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

Position switch, 1early N/O+1late N/C, wide, IP65_x, plungerPosition switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Rounded plunger, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Design: EN 50041 Form B, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Colour Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947Delivery program
Basic functionPosition switches
Safety position switchesPart group referenceAT4Product rangeRounded plungerDegree of ProtectionIP65FeaturesComplete unitAmbient temperature-25 - +70 °CDesignEN 50041 Form BApprovalContactsN/O =

Normally open1 N/ON/C = Normally closed1 NCNotes= safety function, by positive opening to IEC/EN 60947-5-1Contact sequenceContact travel? = Contact closed? = Contact openPositive opening (ZW)yesColourEnclosure coversGreyEnclosure coversHousingInsulated materialConnection typeScrew terminalNotesFor degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length.Technical data GeneralStandardsIEC/EN 60947Climatic proofingDamp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30Ambient temperature-25 - +70 °CMounting positionAs requiredDegree of ProtectionIP65Terminal capacitiesSolid1 x (0.75 - 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AT4/11-2/IA/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.