

**INDUSTRIAL COMPONENT DATA**

# Atlantic LED II O HB CG-S 40071355607 EATON ELECTRIC

## Atlantic LED II OR HB CG-S

Brand: EATON - MOELLER | Manufacturer Part Number: Atlantic LED II O HB CG-S



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | EATON - MOELLER           |
| MPN / Reference | Atlantic LED II O HB CG-S |
| Catalog number  | 40071355607               |
| Category        | Emergency luminaire       |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-E6C01384AE             |
| Generated       | 2026-08-06                |

### Product Overview

Atlantic LED II OR HB CG-S

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

### Additional Product Information

**General specifications**

Product Name Eaton Atlantic LED CG-S Emergency luminaire Catalog Number 40071355607 Ean 4012539357773 Product Length/Depth 304 mm Product Height 62 mm Product Width 136 mm Product Weight 1.5 kg Certifications Ec Product Specifications

Permissible ambient temperature - min -20 °C Permissible ambient temperature - max 40 °C Degree of impact resistance (IK) IK 09 Outdoor use compliance True Degree of protection Ip66 Mode Maintained / Non-Maintained (M/NM) Lamp type LED not exchangeable With light source True Lamp power 3.2 W Monitoring equipment Safety module for monitoring (central feeded system) Power supply system Central (central battery) Voltage type AC/DC Current Consumption At 220V DC 27 mA Apparent Power At Mains Operation 8.5 VA Effective power at mains operation 5 W Power factor .588 With remote switch connection True Reserve-polarity protected True Connection type Plug-in connection Type of wiring Suitable for through wiring Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Nominal voltage DC 220 V Rated ambient temp acc. IEC62722-2-1 - Min -20 °C Rated ambient temp acc. IEC62722-2-1 - Max 40 °C Inrush current 1.5 A Mounting Method Ceiling surface mounting Material housing Aluminium Color housing Grey Material cover Plastic, transparent Limited surface temperature True Number Of Poles (numeric) 3 Impact strength IK09 Kind of luminaire Safety luminaire for escape route and open area lighting Rated Luminous Flux Acc. IEC 62722-2-1 380...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Atlantic LED II O HB CG-S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.