

INDUSTRIAL COMPONENT DATA

AUX1NO+1NC-BOX3 6101137 Y8-6101137 EATON ELECTRIC

Auxiliary contact, 1 N/O + 1N/C, for DDC + QSA, Box3

Brand: EATON - MOELLER | Manufacturer Part Number: AUX1NO+1NC-BOX3



Manufacturer	EATON - MOELLER
MPN / Reference	AUX1NO+1NC-BOX3
Catalog number	Y8-6101137
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-5C175827B7
Generated	2026-08-06

Product Overview

Auxiliary contact, 1 N/O + 1N/C, for DDC + QSA, Box3

AUX1NO+1NC-BOX3

Auxiliary contact, Switching duty 6 A, 230 V AC, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: DDC..., QSA..., Information about equipment supplied: including connection materials

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton Accessory Auxiliary contact Catalog Number 6101137 Model Code AUX1NO+1NC-BOX3 EAN 8711426214880 Product Length/Depth 50 mm Product Height 5 mm Product Width 50 mm Product Weight 0.1 kg

Compliances CE Catalog Notes Switching duty 6 A, 230 V AC Features & Functions

Electric connection type Screw connection General

Accessories Connection materials included with supplied equipment. Model Top mounting Mounting method Front fastening

Type Auxiliary contact Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 6 A Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole,

current-dependent P_{vid} 0.11 W Rated operational current for specified heat dissipation (I_n) 6 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. ef...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AUX1NO+1NC-BOX3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.