

INDUSTRIAL COMPONENT DATA

Z-AHK 248433 Y7-248433 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, 4A, 250V AC

Brand: EATON - MOELLER | Manufacturer Part Number: Z-AHK



Manufacturer	EATON - MOELLER
MPN / Reference	Z-AHK
Catalog number	Y7-248433
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-3967955C5A
Generated	2026-08-05

Product Overview

Auxiliary contact, 1N/O+1N/C, 4A, 250V AC

Z-AHK

Eaton Distribution parts. Auxiliary contact, 1N/O+1N/C, 4A, 250V AC

PLS., PKDM, PFHM-2p, + 1N/O for 1N/C, 0.5auxiliary contacts for PLS., PKDM, PFHM-2p, 1N/O+1N/C, 0.5 SU auxiliary contact, 1N/O+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248433 Model Code Z-AHK EAN 4015082484330 Product Length/Depth 80 mm Product Height 75 mm Product Width 8.8 mm Product Weight 0.038 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Auxiliary contacts Used with Auxiliary contacts

Accessory for combined residual current/power circuit breaker

Accessory

Accessory for miniature circuit breaker

Accessory for residual current circuit breaker Mounting method For fitting on left to: LS, FI/LS Additional equipment required

Auxiliary switch Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 Voltage type AC Functions Auxiliary switch Device fitting Universal Rated operational voltage (Ue) - max 230 V Rated switch current 3 A Suitable for current of main contact unit - max 4 A ETIM for 248433 Modular devices for distribution board/surface mounting (EC001286)

Feature Name
Feature Value
Device fitting (EF007826)
Universal
Function (EF000030)
Auxiliary switch
Width in number of modular spacings (EF002950)
0.5
Number of contacts as normally open contact (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-AHK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.