

INDUSTRIAL COMPONENT DATA

Z-HK 248432 Y7-248432 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, 8A, 250V AC

Brand: EATON - MOELLER | Manufacturer Part Number: Z-HK



Manufacturer	EATON - MOELLER
MPN / Reference	Z-HK
Catalog number	Y7-248432
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-8F06BB4AFA
Generated	2026-08-05

Product Overview

Auxiliary contact, 1N/O+1N/C, 8A, 250V AC

Z-HK

Eaton Distribution parts. Auxiliary contact, 1N/O+1N/C, 8 A, 250 V AC

PFIM, PFHM-4p, dRCM, PFR, + 1N/O for 1N/C, 0.5auxiliary contacts, for PFIM, PFHM-4p, dRCM, PFR, 1N/O+1N/C, 0.5 SU auxiliary contact, 1N/O+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248432 Model Code Z-HK EAN 4015082484323 Product Length/Depth 80 mm Product Height 65.5 mm Product Width 8.8 mm Product Weight 0.04 kg Compliances RoHS conform Certifications EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for industrial and advanced commercial applications Accessory/spare part type Auxiliary contacts Used with Auxiliary contacts

Accessory for residual current circuit breaker

Accessory Mounting method For fitting on left to: FI Additional equipment required Auxiliary switch Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Number of contacts

(change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1

Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 Voltage type AC Functions Auxiliary switch
Device fitting Earth leakage switch Rated operational voltage (Ue) - max 230 V Rated switch current 3 A Suitable for current
of main contact unit - max 8 A

ETIM for 248432 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Earth leakage switch

Function (EF000030)

Auxiliary switch

Width in number of modular spacings (EF002950)

0.5

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

1

Number of contacts....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-HK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.