

INDUSTRIAL COMPONENT DATA

Z-SC 248862 Y7-248862 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SC



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SC
Catalog number	Y7-248862
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-CCD8B18B4C
Generated	2026-08-04

Product Overview

Auxiliary contact, 1N/O+1N/C

Z-SC

Eaton Distribution parts. Auxiliary contact, 1N/O+1N/C

Auxiliary contact for installation contactor, rated insulation voltage 440V AC, rated operational current at AC15 220-240V: 3A, function: 1 N/O and 1 N/C, standard front dimension 45 mm, mounting width 0.5 space units (8.75mm), top-hat rail mounting, type conform to IEC 61095, EN 61095, VDE 0660, IEC 60947-4-1_x, EN 60947-4-1, VDE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts

Catalog Number 248862

Model Code Z-SC

EAN 4015082488628

Product Length/Depth 87.5 mm

Product Height 60 mm

Product Width 8.75 mm

Product Weight 0.026 kg

Compliances RoHS conform

Product specifications

Equipment heat dissipation, current-dependent 0 W

Voltage type AC

Functions Auxiliary switch

Static heat dissipation, non-current-dependent 0 W

Additional equipment required Auxiliary switch

Ambient operating temperature - max 60 °C

Ambient operating temperature - min -40 °C

Assembly width 0.5 TE

Heat dissipation per pole, current-dependent 0.5 W

Main contact unit current rating - max 63 A

Number of contacts (change-over contacts) 0

Number of contacts (normally closed contacts) 1

Number of contacts (normally open contacts) 1

Number of poles at main contact unit - max 4

Number of switches (fault signal) 0

Rated operational current for specified heat dissipation (In) 3 A

Rated operational voltage (Ue) - max 230 V

Rated switch current 3 A

Device fitting Auxiliary switch / relay

ETIM for 248862 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Auxiliary switch / relay

Function (EF000030)

Auxiliary switch

Width in number of modular spacings (EF002950)

0.5

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as change-over contact (EF008257)

0

Number of fault-signal switches....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.