

INDUSTRIAL COMPONENT DATA

AUX1NO+1NC-BOX012 6028293 Y8-6028293 EATON
ELECTRIC Auxiliary contact, 1N / O + 1N / C, for DDC + QSA
Box0 /..

Brand: EATON - MOELLER | Manufacturer Part Number: AUX1NO+1NC-BOX012



Manufacturer	EATON - MOELLER
MPN / Reference	AUX1NO+1NC-BOX012
Catalog number	Y8-6028293
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-E04C8B5014
Generated	2026-08-06

Product Overview

Auxiliary contact, 1N / O + 1N / C, for DDC + QSA; Box0 / 1/2

AUX1NO+1NC-BOX012

Eaton Auxiliary contact, 1 N/O + 1N/C, for DDC + QSA, Box0/1/2

Auxiliary contact, Switching duty 6 A, 230 V AC, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: DDC..., QSA..., Information about equipment supplied: incl. adapter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton Accessory Auxiliary contact Catalog Number 6028293 Model Code AUX1NO+1NC-BOX012 EAN 8711426851627 Product Length/Depth 160 mm Product Height 10 mm Product Width 100 mm Product Weight 0.026 kg

Compliances CE Catalog Notes Switching duty 6 A, 230 V AC Features & Functions

Electric connection type Screw connection General

Accessories Adapter included with supplied equipment. Model Top mounting Mounting method Front fastening Type

Auxiliary contact Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 4 A Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0.11 W Rated operational current for specified heat dissipation (I_n) 6 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AUX1NO+1NC-BOX012 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.