

INDUSTRIAL COMPONENT DATA

AUX1NO+1NC DMVS160-2000 1314736 Y8-1314736 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, for DMVS160N/DMV250-2..

Brand: EATON - MOELLER | Manufacturer Part Number: AUX1NO+1NC DMVS160-2000



Manufacturer	EATON - MOELLER
MPN / Reference	AUX1NO+1NC DMVS160-2000
Catalog number	Y8-1314736
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-1F96F19488
Generated	2026-08-06

Product Overview

Auxiliary contact, 1N/O+1N/C, for DMVS160N/DMV250-2000

AUX1NO+1NC DMVS160-2000

Auxiliary contact, Switching duty 6 A, 230 V AC, 2 auxiliary contacts per DMV, mountable, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: DMVS160N..., DMV250N..., DMV400N..., DMV630N..., DMV1000N..., DMV1250N..., DMV1600N..., DMV2000N..., Rear mounting, Information about equipment supplied: including connection materials

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMV Accessory Auxiliary contact Catalog Number 1314736 Model Code

AUX1NO+1NC DMVS160-2000 EAN 8711426531765 Product Length/Depth 210 mm Product Height 10 mm Product Width 120 mm Product Weight 0.021 kg Compliances CE Catalog Notes Switching duty 6 A, 230 V AC Features & Functions

Electric connection type Screw connection Fitted with: 2 auxiliary contacts per DMV, mountable General

Accessories Connection materials included with supplied equipment. Model Top mounting Mounting method Front fastening

Type Auxiliary contact Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 6 A Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0.11 W Rated operational current for specified heat dissipation (I_n) 6 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AUX1NO+1NC DMVS160-2000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.