

INDUSTRIAL COMPONENT DATA

HI11-P1/P3Z 062031 Y7-62031 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, for P1-P3

Brand: EATON - MOELLER | Manufacturer Part Number: HI11-P1/P3Z



Manufacturer	EATON - MOELLER
MPN / Reference	HI11-P1/P3Z
Catalog number	Y7-62031
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-5BEF99A792
Generated	2026-08-06

Product Overview

Auxiliary contact, 1N/O+1N/C, for P1-P3

Auxiliary Contact Module 1 NO + 1 NC For P1-.../Z P3-.../Z

Eaton Moeller® series P1 Auxiliary contact, 1 N/O, 1 NC, For use with P1, P3, intermediate

Auxiliary contact, Product range: Accessories, Part group reference: P1, P3, Late-break switching-on behavior, early-make switching-off behavior, The N/O is always connected as a load-shedding contact., For left and/or right side mounting, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: P1-.../Z, .../V, .../I2, .../IVS, P3-63/Z, .../V, .../I4, .../IVS, P3-100/Z, .../V, .../I5, .../IVS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Accessory Auxiliary contact Catalog Number 062031 Model Code HI11-P1/P3Z
EAN 4015080620310 Product Length/Depth 41 mm Product Height 83 mm Product Width 15 mm Product Weight 0.04 kg
Certifications CSA-C22.2 No. 14-05

UL File No.: E36332

CSA Class No.: 3211-05

CSA

UL Category Control No.: NLRV

UL 508

CSA File No.: 012528

IEC/EN 60947-5

UL

CE Features & Functions

Electric connection type Screw connection General

Model Top mounting Mounting method Side mounting Mounting position Right side

Left side Product category Accessories Type Auxiliary contact Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.5 - 1.5) mm², ferrules to DIN 46228

2 x (0.5 - 1.5) mm², ferrules to DIN 46228 Terminal capacity (solid) 2 x (0.75 - 1.5) mm²

1 x (0.75 - 2.5) mm² Stripping length (main cable) 7.5 mm Tightening torque 1 Nm, Screw terminals Electrical rating

Rated insulation voltage (Ui) 500 V Rated operational current (Ie) 0.55 A at DC-13, 250 V Rated operational current (Ie) at

AC-15, 220 V, 230 V, 240 V 6 A Rated operational current (Ie) at DC-13, 125 V 1.1 A Rated uninterrupted current (Iu) 10 A

Short-circuit rating

Short-circuit protection rating Max. 10 A gG/gL, Fuse, Auxiliary contacts Contacts

Control circuit reliability 1 failure per 100,000 switching operations statistically determined, at 24 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / HI11-P1/P3Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.