

INDUSTRIAL COMPONENT DATA

QMAUX1NO+1NC40/63 1319851 Y8-1319851 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, for QM40/63

Brand: EATON - MOELLER | Manufacturer Part Number: QMAUX1NO+1NC40/63



Manufacturer	EATON - MOELLER
MPN / Reference	QMAUX1NO+1NC40/63
Catalog number	Y8-1319851
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-616DA0503C
Generated	2026-08-06

Product Overview

Auxiliary contact, 1N/O+1N/C, for QM40/63

QMAUX1NO+1NC40/63

Eaton Moeller® series QM Auxiliary contact, 1N/O+1N/C, for QM40/63

Auxiliary contact, Switching duty 6 A, 230 V AC, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: QM40..., QM63...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton Moeller® series QM Accessory Auxiliary contact Catalog Number 1319851 Model Code QMAUX1NO+1NC40/63 EAN 8711426101371 Product Length/Depth 160 mm Product Height 5 mm Product Width 100 mm Product Weight 0.028 kg Compliances CE Catalog Notes Switching duty 6 A, 230 V AC Features & Functions Electric connection type Screw connection General Mounting method Side mounting Type Auxiliary contact Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Terminal capacities Terminal capacity (solid) 0.75 - 2.5 mm² Stripping length (main cable) 9 mm Electrical rating Rated operational current (I_e) at AC-15, 220 V, 230 V, 240 V 3 A Contacts Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0.11 W Rated operational current for specified heat dissipation (I_n) 6 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QMAUX1NO+1NC40/63 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.