

## INDUSTRIAL COMPONENT DATA

# QMAUX1NO+1NC80/100 1319853 Y8-1319853 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, for QM80/100

Brand: EATON - MOELLER | Manufacturer Part Number: QMAUX1NO+1NC80/100



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | QMAUX1NO+1NC80/100      |
| Catalog number  | Y8-1319853              |
| Category        | Auxiliary contact block |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-51F2ED6769           |
| Generated       | 2026-08-06              |

## Product Overview

Auxiliary contact, 1N/O+1N/C, for QM80/100

QMAUX1NO+1NC80/100

Eaton Moeller® series QM Auxiliary contact, 1N/O+1N/C, for QM80/100

Auxiliary contact, Switching duty 6 A, 230 V AC, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: QM80..., QM100...

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; DUMECO Switch-Disconnectors

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series QM Accessory Auxiliary contact Catalog Number 1319853 Model Code QMAUX1NO+1NC80/100 EAN 8711426251373 Product Length/Depth 170 mm Product Height 5 mm Product Width 100 mm Product Weight 0.031 kg Compliances CE Catalog Notes Switching duty 6 A, 230 V AC Features & Functions Electric connection type Screw connection General Mounting method Side mounting Type Auxiliary contact Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Terminal capacities Terminal capacity (solid) 0.75 - 2.5 mm<sup>2</sup> Stripping length (main cable) 9 mm Electrical rating Rated operational current (I<sub>e</sub>) at AC-15, 220 V, 230 V, 240 V 3 A Contacts Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Design verification

Equipment heat dissipation, current-dependent  $P_{vid}$  0 W Heat dissipation capacity  $P_{diss}$  0 W Heat dissipation per pole, current-dependent  $P_{vid}$  0.11 W Rated operational current for specified heat dissipation ( $I_n$ ) 6 A Static heat dissipation, non-current-dependent  $P_{vs}$  0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnorm...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QMAUX1NO+1NC80/100 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.