

INDUSTRIAL COMPONENT DATA

DILP800-XHI-SA 207471 XTCFAXSCN11 EATON ELECTRIC

Auxiliary contact, 1N/O+1N/C, side exterior, screw connecti..

Brand: EATON - MOELLER | Manufacturer Part Number: DILP800-XHI-SA



Manufacturer	EATON - MOELLER
MPN / Reference	DILP800-XHI-SA
Catalog number	XTCFAXSCN11
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-9B4F6BB640
Generated	2026-08-06

Product Overview

Auxiliary contact, 1N/O+1N/C, side exterior, screw connection

Auxiliary contacts 1 NO + 1 NC External side Screw connection

Auxiliary contact module, I_{th}= 16 A, 1 N/O, 1 NC, Side mounted, Spring-loaded terminals, DILP

Auxiliary contact module, Function: for standard applications, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e= 4 A, Rated operational current AC-15 380 V 400 V 415 V: I_e= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILP250..., DILP315..., DILP500..., DILP630..., DILP800..., Type: Side-mounting auxiliary contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

Auxiliary contact module, I_{th}= 16 A, 1 N/O, 1 NC, Side mounted, Spring-loaded terminals, DILP
Auxiliary contact module, Function: for standard applications, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e= 4 A, Rated operational current AC-15 380 V 400 V 415 V: I_e= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILP250..., DILP315..., DILP500..., DILP630..., DILP800..., Type: Side-mounting auxiliary contacts
Delivery program

Accessories
Auxiliary contact modules
Function for standard applications
Connection technique Spring-loaded terminals
Rated operational current Conventional free air thermal current, 1 pole Open at 60 °C [I_{th}] 16 A AC-15 220 V 230 V 240 V [I_e] 4 A AC-15 380 V 400 V 415 V [I_e] 4 A
Contacts N/O = Normally open 1 N/O N/C = Normally closed 1 NC
Mounting type Side mounted
Contact sequence For use with DILP250...

DILP315...

DILP500...

DILP630...

DILP800...TypeSide-mounting auxiliary contactsTechnical data

GeneralStandardsIEC/EN 60947, VDE 0660, UL, CSAComponent lifespanat Ue= 230 V, AC-15, 3 A [Operations]0.5 x 106Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-40 - +70 °CAmbient temperatureEnclosed- 25 - 40

°CAmbient temperatureAmbient temperature, storage- 40 - 80 °CWeight0.05 kgContactsN/C contact (not late-break contact) suitable as a mirror contact (to IEC/EN 60947-4-1 Annex F)DILP250 - DILP800Rated impulse w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILP800-XHI-SA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.