

INDUSTRIAL COMPONENT DATA

11DILEM 010080 Y7-10080 EATON ELECTRIC Auxiliary contact, 1N/O+1N/C, surface mounting, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: 11DILEM



Manufacturer	EATON - MOELLER
MPN / Reference	11DILEM
Catalog number	Y7-10080
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-A6D48F76B2
Generated	2026-08-05

Product Overview

Auxiliary contact, 1N/O+1N/C, surface mounting, screw connection

Auxiliary Contact Block 1 NO + 1 NC Front Mount Connection To

Eaton Moeller® series DILEM Auxiliary contact module, 1 N/O, 1 NC, Front fixing, Screw terminals, DILE(E)M

Auxiliary contact module, Connection technique: Screw terminals, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Degree of Protection: IP20, For use with: DILEM-10(-G)(...), DILEM-4(-G)(...), DILEEM-10(-G)(...), DILEM12-10(-G)(...)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILEM Accessory Auxiliary contact module Catalog Number 010080 Model Code 11DILEM EAN 4015080100805 Product Length/Depth 36 mm Product Height 32 mm Product Width 45 mm Product Weight 0.03 kg Certifications UL Category Control No.: NKCR
VDE 0660
CSA
CSA Class No.: 3211-03
UL
CSA File No.: 012528
IEC/EN 60947

CE

CSA-C22.2 No. 14-05

UL File No.: E29184

IEC/EN 60947-4-1

UL 508 Features & Functions

Electric connection type Screw connection Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Fitted with: Interlocked opposing contacts Functions For standard applications General

Lifespan, mechanical 10,000,000 Operations (AC operated)

20,000,000 Operations (DC operated)

200,000 Operations (at 240 V, AC-15)

150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A) Model Top mounting Mounting method Front fastening Mounting position As required (except vertical with terminals A1/A2 at the bottom) Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance 10 g, N/O contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 8 g, N/C contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Climatic environmental c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 11DILEM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.