

INDUSTRIAL COMPONENT DATA

ASAUXSC-SPM 131785 Y7-131785 EATON ELECTRIC

Auxiliary contact, 1W, 2A, 250V AC

Brand: EATON - MOELLER | Manufacturer Part Number: ASAUXSC-SPM



Manufacturer	EATON - MOELLER
MPN / Reference	ASAUXSC-SPM
Catalog number	Y7-131785
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-8E4138C307
Generated	2026-08-04

Product Overview

Auxiliary contact, 1W, 2A, 250V AC

ASAUXSC-SPM

Eaton Distribution parts. Auxiliary contact, 1W, 2A, 250V AC

Type similar to IEC 60947-5-1, can be retrofitted, can be used for SPMT2PA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 131785 Model Code ASAUXSC-SPM EAN 5019586148957

Product Length/Depth 80 mm Product Height 65.5 mm Product Width 8.8 mm Product Weight 0.05 kg Compliances RoHS conform Product specifications

Type Application Open areas

Residential buildings

Utility buildings

Used with SPMT2PA

Accessory

Auxiliary contact Additional equipment required Auxiliary switch Assembly width 0.5 TE Number of contacts (change-over contacts) 1 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Voltage type AC Functions Auxiliary switch Device

fitting Other Rated operational voltage (Ue) - max 250 V Rated switch current 2 A Suitable for current of main contact unit - max 0 A

ETIM for 131785 Modular devices for distribution board/surface mounting (EC001286)

Feature Name

Feature Value

Device fitting (EF007826)

Other

Function (EF000030)

Auxiliary switch

Width in number of modular spacings (EF002950)

0.5

Number of contacts as normally open contact (EF008256)

1

Number of contacts as normally closed contact (EF008255)

1

Number of contacts as change-over contact (EF008257)

1

Number of fault-signal switches (EF007613)

0

Rated switch current (EF006706)

2 A

Rated voltage (EF000228)

250 V

Voltage type (EF000187)

AC

With auto test for earth leakage function (EF008727)

No

Suitable for max. number of poles main contact unit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ASAXSC-SPM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.