

INDUSTRIAL COMPONENT DATA

NZM4-XHIV 266172 Y7-266172 EATON ELECTRIC Auxiliary contact, 2early N/O, operates as an early-make contact

Brand: EATON - MOELLER | Manufacturer Part Number: NZM4-XHIV



Manufacturer	EATON - MOELLER
MPN / Reference	NZM4-XHIV
Catalog number	Y7-266172
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-834B305CDD
Generated	2026-08-06

Product Overview

Auxiliary contact, 2early N/O, operates as an early-make contact

NZM4-XHIV

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. For interlocking and load shedding circuits, as well as for early make of the undervoltage release in main switch/emergency switching off applications. Not in conjunction with undervoltage release NZM...XU..., Shunt release NZM...XA.. or remote operator NZM...XR.. Early make (manual operation) approx. 20..90ms. Can be used for: NZM4(-4), N(N/O)4(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Auxiliary contact, 2early N/O, operates as an early-make contactOptional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. For interlocking and load shedding circuits, as well as for early make of the undervoltage release in main switch/emergency switching off applications. Not in conjunction with undervoltage release NZM...XU..., Shunt release NZM...XA.. or remote operator NZM...XR.. Early make (manual operation) approx. 20..90ms. Can be used for: NZM4(-4), N(N/O)4(-4)

General specificationsProduct nameEaton Moeller series NZM auxiliary contactPart

no.NZM4-XHIVEAN4015082661724Product Length/Depth107 millimetreProduct height51 millimetreProduct width64 millimetreProduct weight0.129 kilogramCompliancesRoHS conformCertificationsCSA (Class No. 1437-01)

CSA (File No. 22086)

CSA certified

UL (Category Control Number DIHS)

CSA-C22.2 No. 5-09

UL489

IEC60947

UL listed

UL (File No. E140305)

CE markingProduct TradenameNZMProduct TypeAccessoriesProduct Sub TypeAuxiliary contactDelivery programSpecial featuresC300/R300 (auxiliary contacts, UL/CSA, pilot duty)Used withFAZ-B6 (max. miniature circuit breaker)Technical Data - ElectricalVoltage rating at DC220 V DCVoltage rating at AC500 V ACRated operational current2.5 A at 240 V AC (UL/CSA)

1 A at 250 V DC (UL/CSA)Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V4 AConventional thermal current Ith...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM4-XHIV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.