

INDUSTRIAL COMPONENT DATA

AUX2NO+2NCDCM/DMM 1314301 Y8-1314301 EATON ELECTRIC Auxiliary contact, 2N/O+2N/C for DMM part no.

Brand: EATON - MOELLER | Manufacturer Part Number: AUX2NO+2NCDCM/DMM



Manufacturer	EATON - MOELLER
MPN / Reference	AUX2NO+2NCDCM/DMM
Catalog number	Y8-1314301
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-FC30652C96
Generated	2026-08-05

Product Overview

Auxiliary contact, 2N/O+2N/C for DMM part no.

AUX2NO+2NCDCM/DMM

Auxiliary contact, Switching duty 16 A, 250 V AC, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, For use with: DCM, DMM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton Accessory Auxiliary contact Catalog Number 1314301 Model Code AUX2NO+2NCDCM/DMM EAN 8711426163652 Product Length/Depth 170 mm Product Height 2 mm Product Width 190 mm Product Weight 0.06 kg

Compliances CE Catalog Notes Switching duty 16 A, 250 V AC Features & Functions

Electric connection type Screw connection General

Model Top mounting Mounting method Front fastening Type Auxiliary contact Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 6 A Contacts

Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 2 Number of contacts (normally open contacts) 2 Design verification

Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 0.11 W Rated operational current for specified heat dissipation (In) 16 A Static heat dissipation,

non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AUX2NO+2NCDCM/DMM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.