

INDUSTRIAL COMPONENT DATA

22DILEM 010112 Y7-10112 EATON ELECTRIC Auxiliary contact, 2N/O+2N/C, surface mounting, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: 22DILEM



Manufacturer	EATON - MOELLER
MPN / Reference	22DILEM
Catalog number	Y7-10112
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-B3FA2163B4
Generated	2026-08-05

Product Overview

Auxiliary contact, 2N/O+2N/C, surface mounting, screw connection

Auxiliary Contact Block 2 NO + 2 NC Front Mount Connection To

Eaton Moeller® series DILEM Auxiliary contact module, 4 pole, 2 N/O, 2 NC, Front fixing, Screw terminals, DILE(E)M Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50012, Switching elements according to EN 50012 are to be preferred., Version E combinations correspond to EN 50011 and are to be preferred., Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 2 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Mounting type: Front fixing, For use with: DILEM-10(-G)(...), DILEM-4(-G)(...), DILEEM-10(-G)(...), DILEM12-10(-G)(...), Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILEM Accessory Auxiliary contact module Catalog Number 010112 Model Code 22DILEM EAN 4015080101123 Product Length/Depth 36 mm Product Height 32 mm Product Width 45 mm Product Weight 0.04 kg Certifications CSA Class No.: 3211-03
CSA File No.: 012528
IEC/EN 60947

UL
UL 508
IEC/EN 60947-4-1
UL Category Control No.: NKCR
UL File No.: E29184
VDE 0660
CSA
CSA-C22.2 No. 14-05
CE Features & Functions
Electric connection type Screw connection Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Fitted with: Interlocked opposing contacts Functions For standard applications
Number of poles Four-pole General
Lifespan, mechanical 20,000,000 Operations (DC operated)
200,000 Operations (at 240 V, AC-15)
10,000,000 Operations (AC operated)
150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A) Model Top mounting Mounting method Front fastening Mounting position As required (except vertical with terminals A1/A2 at the bottom) Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance 10 g, N/O contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
8 g, N/C contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 22DILEM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.