

## INDUSTRIAL COMPONENT DATA

# 04DILE 010256 Y7-10256 EATON ELECTRIC Auxiliary contact, 4 N/C, surface mounting, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: 04DILE



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | 04DILE                  |
| Catalog number  | Y7-10256                |
| Category        | Auxiliary contact block |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-3ECD4EBBE2           |
| Generated       | 2026-08-03              |

## Product Overview

Auxiliary contact, 4 N/C, surface mounting, screw connection

Auxiliary Contact Block 4 NC Front Mount Connection To

Eaton Moeller® series DILE Auxiliary contact module, 4 pole, 4 NC, Front fixing, Screw terminals, DILE(E)M, DILER Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Switching elements according to EN 50012 are to be preferred., Version E combinations correspond to EN 50011 and are to be preferred., Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: I<sub>e</sub>= 4 A, Rated operational current AC-15 380 V 400 V 415 V: I<sub>e</sub>= 2 A, Contacts N/C = Normally closed: 4 NC, Mounting type: Front fixing, For use with: DILEM-10(-G)(...), DILEM-01(-G)(...), DILEM-4(-G)(...), DILER40(-G), DILER31(-G), DILER22, DILEEM-10(-G)(...), DILEEM-01(-G)(...), DILEM12-10(-G)(...), DILEM12-01(-G)(...), Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILE Accessory Auxiliary contact module

Catalog Number 010256

Model Code 04DILE

EAN 4015080102564

Product Length/Depth 36 mm

Product Height 32 mm

Product Width 45 mm

Product Weight 0.04 kg

Certifications CE

IEC/EN 60947-4-1

CSA-C22.2 No. 14-05

UL

CSA Class No.: 3211-03

CSA File No.: 012528

UL 508

IEC/EN 60947

CSA

UL Category Control No.: NKCR

UL File No.: E29184

VDE 0660

Features & Functions

Electric connection type Screw connection

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)

Fitted with: Interlocked opposing contacts

Switching elements according to EN 50005

Functions For standard applications

Number of poles Four-pole

General

Lifespan, mechanical 10,000,000 Operations (AC operated)

20,000,000 Operations (DC operated)

200,000 Operations (at 240 V, AC-15)

150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A)

Model Top mounting

Mounting method Front fastening

Mounting position As required (except vertical with terminals A1/A2 at the bottom)

Operating frequency 9000 Operations/h

Overvoltage category III

Pollution degree 3

Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp) 6000 V AC

Shock resistance 10 g, N/O contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

8 g, N/C contact, Mechanical, according to IEC/EN...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 04DILE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.