

INDUSTRIAL COMPONENT DATA

Z-IHK-NA 113895 Y7-113895 EATON ELECTRIC Auxiliary contact, for FAZ-NA, FAZ-RT, 1N/O+1N/C, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-IHK-NA



Manufacturer	EATON - MOELLER
MPN / Reference	Z-IHK-NA
Catalog number	Y7-113895
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-D800ED6F4E
Generated	2026-08-06

Product Overview

Auxiliary contact, for FAZ-NA, FAZ-RT, 1N/O+1N/C, 0.5HP

Z-IHK-NA

Eaton Distribution parts. Auxiliary contact, for FAZ-NA, FAZ-RT, 1N/O+1N/C, 0.5HP

FAZ-NA, FAZ-RT, + 1N/O for 1N/C, 0.5auxiliary contacts, for FAZ-NA, FAZ-RT, 1N/O+1N/C, 0.5 SU auxiliary contact, 1N/O+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 113895 Model Code Z-IHK-NA EAN 4015081134052 Product Length/Depth 96 mm Product Height 75 mm Product Width 8.8 mm Product Weight 0.048 kg Compliances RoHS conform Certifications IEC/EN 60898

CSA (File No. 204453)

CSA-C22.2 No. 5-09

UL 489

North America (UL listed, CSA certified)

CE marking

CSA (Class No. 1437-01)

UL (Category Control Number DIHS, DIHS7)

UL (File No. E257181)

EN45545-2

IEC 61373 Product specifications

Type Application Switchgear for export to North America (UL-listed) Voltage rating 250 V AC Amperage Rating 6 A

Accessory/spare part type Auxiliary contacts Degree of protection IP20 (IEC)

UL/CSA Type: -

IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Auxiliary contacts

Accessory for miniature circuit breaker

Accessory Rated impulse withstand voltage (Uimp) 4 kV Mounting method For fitting on left to: FAZ-NA, FAZ-RT Additional equipment required Auxiliary switch Terminal protection Busbar tag shroud to BGV A3 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Conventional thermal current ith of auxiliary contacts (1-pole, open) 6 A Enclosure width 80 mm Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-IHK-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.