

INDUSTRIAL COMPONENT DATA

FAZ-XHIN11 286054 Y7-286054 EATON ELECTRIC Auxiliary contact, for FAZ, PKNM, 1N/O+1N/C, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-XHIN11



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-XHIN11
Catalog number	Y7-286054
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-DC7CE23EF0
Generated	2026-08-06

Product Overview

Auxiliary contact, for FAZ, PKNM, 1N/O+1N/C, 0.5HP

FAZ-XHIN11

Eaton Distribution parts. Auxiliary contact, for FAZ, PKNM, 1N/O+1N/C, 0.5HP

FAZ, PKNM, + 1N/O for 1N/C, 0.5auxiliary contacts, for FAZ, PKNM, 1N/O+1N/C, 0.5 SU auxiliary contact, 1N/O+1N/CSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 286054 Model Code FAZ-XHIN11 EAN 4015082860547 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 8.8 mm Product Weight 0.046 kg Compliances RoHS conform

Certifications UL (File No. E177451)

North America (UL listed, certified by UL for use in Canada)

IEC/EN 60898

CSA (Class No. 3215-30)

UL 1077

CE marking

UL (Category Control Number QVNU2, QVNU9)

IEC/EN 60947-2

CSA-C22.2 No. 235

EN45545-2

IEC 61373 Catalog Notes & 1NC Product specifications

Used with Accessory

Accessory for miniature circuit breaker Type Voltage rating 250 V AC Amperage Rating 6 A Accessory/spare part type

Auxiliary contacts Degree of protection UL/CSA Type: -

IP40

IP20 (IEC) Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Rated impulse withstand voltage (Uimp) 2.5 kV Mounting method Max. 2 x on MCB Additional equipment required Auxiliary switch Admissible back-up fuse - max 6 A gL Terminal protection Protection against electric shock to IEC 536 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Conventional thermal current Ith of auxiliary contacts (1-pole, open) 6 A Enclosure width 80 mm Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 1 Number of contacts (normally open contacts) 1 Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 Rated conditi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-XHIN11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.