

INDUSTRIAL COMPONENT DATA

FAZ-XHINW1 286055 Y7-286055 EATON ELECTRIC Auxiliary contact, for FAZ, PKNM, 1N/O+1N/C, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-XHINW1



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-XHINW1
Catalog number	Y7-286055
Category	Auxiliary device for distribution board devices
Minimum order	10 Pcs
Document ID	EO-7D8E50F9DF
Generated	2026-08-06

Product Overview

Auxiliary contact, for FAZ, PKNM, 1N/O+1N/C, 0.5HP

FAZ-XHINW1

Eaton Distribution parts. Auxiliary breaker, 1W, 3A, 230VAC

FAZ, PKNM, + 1N/O for 1N/C, 0.5auxiliary contacts, for FAZ, PKNM, 1N/O+1N/C, 0.5 SU auxiliary contact, 1WSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 286055 Model Code FAZ-XHINW1 EAN 4015082860554 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 8.8 mm Product Weight 0.046 kg Compliances RoHS conform Certifications CE marking

UL (Category Control Number QVNU2)

UL 1077

IEC/EN 60898

CSA-C22.2 No. 235

IEC/EN 60947-2

UL listed, CSA request filed

UL (File No. E177451)

EN45545-2

IEC 61373 Product specifications

Used with Accessory

Accessory for miniature circuit breaker Type Voltage rating 250 V AC Amperage Rating 6 A Accessory/spare part type

Auxiliary contacts Degree of protection IP40

IP20 (IEC)

UL/CSA Type: - Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Rated impulse withstand voltage (Uimp) 2.5 kV Mounting method Max. 2 x on MCB Additional equipment required Auxiliary switch Admissible back-up fuse - max 6 A gL Terminal protection Protection against electric shock to IEC 536 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Conventional thermal current with of auxiliary contacts (1-pole, open) 6 A Enclosure width 80 mm Number of contacts (change-over contacts) 1 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Number of poles at main contact unit - max 1 Number of switches (fault signal) 0 Rated conditional short-circuit current (Iq) with 6 a back-up fuse 1 kA Rated insulation voltag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-XHINW1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.