

INDUSTRIAL COMPONENT DATA

FAZ-XAM002 262414 Y7-262414 EATON ELECTRIC Auxiliary contact, for FAZ, PKNM, 2W, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-XAM002



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-XAM002
Catalog number	Y7-262414
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-E0BF4821D9
Generated	2026-08-06

Product Overview

Auxiliary contact, for FAZ, PKNM, 2W, 0.5HP

FAZ-XAM002

Eaton Distribution parts. Auxiliary contact, for FAZ, PKNM, 2W, 0.5HP

FAZ, PKNM, for 2W, 0.5auxiliary contacts, for FAZ, PKNM, 2W, 0.5 SU auxiliary contact, 2WSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 262414 Model Code FAZ-XAM002 EAN 4015082624149 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 8.8 mm Product Weight 0.045 kg Compliances RoHS conform Certifications CE marking

UL (File No. E177451)

North America (UL listed, certified by UL for use in Canada)

IEC/EN 60947-2

UL (Category Control Number QVNU2, QVNU8)

CSA-C22.2 No. 235

UL 1077

CSA (Class No. 3215-30)

IEC/EN 60898

EN45545-2

IEC 61373 Product specifications

Type Voltage rating 250 V AC Amperage Rating 4 A Accessory/spare part type Auxiliary contacts Degree of protection

UL/CSA Type: -

IP20 (IEC)

IP40 Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Used with Accessory for miniature circuit breaker

Accessory Rated impulse withstand voltage (Uimp) 2.5 kV Mounting method On MCB Additional equipment required Other

Admissible back-up fuse - max 4 A gL Terminal protection Protection against electric shock to IEC 536 Terminal type Lift

terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE

Conventional thermal current Ith of auxiliary contacts (1-pole, open) 4 A Enclosure width 80 mm Number of contacts

(change-over contacts) 2 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0

Number of poles at main contact unit - max 2 Number of switches (fault signal) 0 Rated conditional short-circuit current (Iq) with 6....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-XAM002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.