

INDUSTRIAL COMPONENT DATA

Z-NHK 248434 Y7-248434 EATON ELECTRIC Auxiliary contact, for PKDM, PFIM, PFR, PFHM, dRCM, 2W, 0.5HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-NHK



Manufacturer	EATON - MOELLER
MPN / Reference	Z-NHK
Catalog number	Y7-248434
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-4D0E5F9CE1
Generated	2026-08-06

Product Overview

Auxiliary contact, for PKDM, PFIM, PFR, PFHM, dRCM, 2W, 0.5HP

Z-NHK

Eaton Distribution parts. Auxiliary contact, for PKDM, PFIM, PFR, PFHM, dRCM, 2W, 0.5HP

PKDM, PFIM, PFR, PFHM, dRCM, for 2W, 0.5auxiliary contacts, for PKDM, PFIM, PFR, PFHM, dRCM, 2W, 0.5 SU

auxiliary contact, 2WSU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 248434 Model Code Z-NHK EAN 4015082484347 Product

Length/Depth 80 mm Product Height 75 mm Product Width 8.8 mm Product Weight 0.045 kg Compliances RoHS conform

Certifications CE marking

CSA (Class No. 1437-01)

UL (File No. E257181)

North America (UL listed, CSA certified)

CSA-C22.2 No. 5-09

UL 489

IEC/EN 60898

UL (Category Control Number DIHS, DIHS7)

CSA (File No. 204453)

EN45545-2

IEC 61373 Product specifications

Used with Trigger signal contact

Accessory

Accessory for combined residual current/power circuit breaker

Accessory for miniature circuit breaker

Accessory for residual current circuit breaker Type Application Switchgear for industrial and advanced commercial applications Voltage rating 230 V AC Amperage Rating 2 A Accessory/spare part type Tripping signal contacts Degree of protection UL/CSA Type: -

IP40

IP20 (IEC) Frame Standard front dimension: 45 mm Frequency rating 50 Hz / 60 Hz Rated impulse withstand voltage

(Uimp) 2.5 kV Mounting method For fitting on right to: FI

For fitting on left to: LS, FI/LS

Can be fitted to left of FAZ-...-NA, FAZ-...-RT, FAZ-XAA-NA... Additional equipment required Signaling switch Admissible back-up fuse - max 6 A gL Terminal protection Busbar tag shroud to BGV A3 Terminal type Lift terminals Ambient operating temperature - max 40 °C Ambient operating temperature - min -5 °C Assembly width 0.5 TE Conventional thermal current Ith of auxiliary contacts (1-pole, open)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-NHK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.