

INDUSTRIAL COMPONENT DATA

DILA-XHIC01-S 115951 XTCEXSABC01 EATON ELECTRIC

Auxiliary contact module, 1 N/C, side, spring clamp connecti..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHIC01-S



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHIC01-S
Catalog number	XTCEXSABC01
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-C9D2A1E1B5
Generated	2026-08-05

Product Overview

Auxiliary contact module, 1 N/C, side, spring clamp connection

Auxiliary contact block 1 NC Side mounting Connection to

Auxiliary contact module, 1 pole, Ith= 16 A, 1 NC, Side mounted, Spring-loaded terminals, DILA, DILM7 - DILM15

Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, 1 pole, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILMC7..., DILMC9..., DILMC12..., DILMC15..., DILAC..., Type: Side-mounting auxiliary contacts , Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > KDIL Accessories
--------------	------------------------------------

Additional Product Information

EL-Nummer (Norway)4110212Auxiliary contact module, 1 pole, Ith= 16 A, 1 NC, Side mounted, Spring-loaded terminals, DILA, DILM7 - DILM15Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for standard applications, 1 pole, Connection technique:

Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: $I_e = 4$ A, Rated operational current AC-15 380 V 400 V 415 V: $I_e = 4$ A, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILMC7..., DILMC9..., DILMC12..., DILMC15..., DILAC..., Type: Side-mounting auxiliary contacts, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, inside the auxiliary contact modules, also for the integrated auxiliary contacts of the DILM 7 - DILM32, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open) Delivery program

Accessories Auxiliary contact modules Description with interlocked opposing contacts

Switching elements according to EN 50005

Version E combinations correspond to EN 50011 and are to be preferred.

The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts. Function for standard applications Number of poles 1 pole Connection technique Spring-loaded terminals Rated operational current...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHIC01-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.