

INDUSTRIAL COMPONENT DATA

DILM1000-XHIV11-SI 278426 Y7-278426 EATON ELECTRIC

Auxiliary contact module 1 NO early-make + 1 NC late-brea..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM1000-XHIV11-SI



Manufacturer	EATON - MOELLER
MPN / Reference	DILM1000-XHIV11-SI
Catalog number	Y7-278426
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-399E6DC08E
Generated	2026-08-05

Product Overview

Auxiliary contact module;1 NO early-make + 1 NC late-break;laterally inside
DILM1000-XHIV11-SI

Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/OE, 1 NCL, Side mounted, Screw terminals, DILM40 - DILM225A

Auxiliary contact module, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 500 V: Ie= 4 A, Contacts N/OE: NO early-make: 1 N/OE, Contacts NCL=NC late-break: 1 NCL, Mounting type: Side mounted, For use with: DILM40 - DILM225A, DILMP63 - DILMP200, DILMF40 - DILMF95, Type: Side-mounting auxiliary contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path | EATON - MOELLER > Contactors more than 170 A

Additional Product Information

EL-Nummer (Norway)4110349Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/OE, 1 NCL, Side mounted, Screw terminals, DILM40 - DILM225AAuxiliary contact module, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 500 V: Ie= 4 A, Contacts N/OE: NO early-make: 1 N/OE, Contacts NCL=NC late-break: 1 NCL, Mounting type: Side mounted, For use with: DILM40 - DILM225A, DILMP63 - DILMP200, DILMF40 - DILMF95, Type: Side-mounting auxiliary contactsDelivery program

AccessoriesAuxiliary contact modulesFunctionfor standard applicationsNumber of poles2 poleConnection techniqueScrew terminalsRated operational currentConventional free air thermal current, 1 poleOpenat 60 °C [Ith]10 AAC-15220 V 230 V

240 V [Ie]4 AAC-15380 V 400 V 415 V [Ie]4 AAC-15380 V 400 V 500 V [Ie]4 AContactsN/OE: NO early-make1
N/OENCL=NC late-break1 NCLMounting typeSide mountedContact sequenceFor use withDILM40 - DILM225A
DILMP63 - DILMP200
DILMF40 - DILMF95TypeSide-mounting auxiliary contactsTechnical data
GeneralStandardsIEC/EN 60947, VDE 0660, UL, CSAComponent lifespanat Ue= 230 V, AC-15, 3 A [Operations]1.3 x
106Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +60 °CAmbient temperatureEnclosed- 25 - 40
°CAmbient temperatureAmbient temperature, storage- 4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM1000-XHIV11-SI with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.